

WindoFix Mount Film - Clear Removable Adhesive

WindoFix is a window graphic mounting film that is visually clear, coated one side with an removable aqueous adhesive, which is protected by an embossed liner which imparts an embossed pattern into the adhesive coating. The other side is coated with aggressive permanent acrylic adhesive.

Suggested applications include the mounting of graphics onto windows in situ. The micro grooves that are formed in the removable adhesive during manufacture allow for easy application resulting in a “no bubble” appearance, because of the removable adhesive any imperfections after application can be removed using a squeegee or by re-applying as the nature of the adhesive allows removal with no residue.

The product is supplied on a 76mm core and is available in widths of 1040, 1300mm and 1530mm

Product Features

Component	Description
Release Liner 1	72gsm White PE Coated Siliconised Release Paper
Adhesive	25µ Acrylic Permanent Pressure Sensitive Adhesive
Carrier	70µ Gloss PVC
Adhesive	25µ Acrylic Removable Pressure Sensitive Adhesive
Release Liner 1	70µ Filmic Textured Release

Other Instructions

The material is ideally stored upright and should be kept free from moisture and excessive exposure to UV before use.

The above data does not constitute a guarantee; specification is given in good faith. End users of this product are urged to test the product in the application and exposure conditions in which the product will be used.

Material Safety Data Sheet

WindoFix Mount Film - Clear Removable Adhesive

Manufacturer: DTL Supplies Ltd

Product Description: WindoFix is a 70µ (micron) clear PVC film coated on one side with an aggressive permanent pressure sensitive adhesive laminated with a 72gsm PE coated siliconised release liner. The other side is coated with a removable aqueous acrylic adhesive, which is protected by an embossed filmic liner. This product is laminated on both sides with 72gsm PE coated siliconised release liner.

Hazards: There are no hazards to man or the environment; the product is stable under normal conditions of use

First Aid:

Ingestion: Rinse mouth immediately with water and seek medical advice

Skin Contact: Not harmful, on contact with the adhesive wash with soap and water

Eye Contact: Rinse eyes with plenty of water

Inhalation: In case of fire, do not breathe fumes

Fire & Explosive Hazards:

Flammability: PVC is a self-extinguishing film. It will burn when in direct contact with a flame or any high temperature ignition source, on removal of the direct flame it will self-extinguish. There is no explosion hazard.

Decomposition: Water vapour (H₂O), Carbon Dioxide (CO₂), Carbon Monoxide (CO) and gaseous Hydrogen Chloride (HCl)

Extinguishing Material: Water, foam, carbon dioxide and dry extinguishers can be used

Fire Fighting Precautions: Hydrogen Chloride is toxic, avoid breathing the fumes

Safe Handling & Use Precautions:

There are no special hazards associated with product if it is handled, stored, processed and disposed of under normal conditions.

Disposal:

Waste disposal should be in accordance local, regional and national legislation

Protective and Control Measures:

There are no protective clothing requirements under normal conditions of use

Toxicology Information:

Providing the material is handled and processed correctly, it is not harmful to health.

Toxicology Information:

This product is not classified as hazardous under transport regulations

Product Specifications are subject to change without prior notice

The information concerning DTL Supplies Ltd products is based upon research which the company believes to be reliable and accurate. Such information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. DTL Supplies Ltd does not accept liability for risks associated with the performance of the materials in application. All DTL Supplies Ltd products are subjected to carefully quality control throughout the manufacturing process and are sold subject to DTL Supplies Ltd standard conditions of sale